


















MODELO	CÉLULA	CAPACIDAD	PRECIO
TPF - 1D	(250 x 250 mm) 	2 - 3 - 5 Kg	
BL (PL-38)	(380 x 380 mm) 	5-7-10-15-20-40Kg	
PL - 50	(500 x 500 mm) 	25 - 50 - 75 - 100 150 - 200 - 250 Kg	
BS - 1	(600 x 600 mm) 	50 - 75 - 100 - 150 200 - 300 - 500 Kg	
BS - 2	(800 x 800 mm) 	150 - 300 - 500 750 - 1000 Kg	
FLEXIÓN		BALANZAS-MONOPLATAFORMAS	
FX-1		10 - 15 - 25 - 50 - 75 100 - 150 - 200 Kg	
FX-2		100 - 150 - 200 - 250 300 - 500 - 750 1000 - 1500 Kg	
TCC-1 (CO-1)		15 - 30 - 50 - 75 - 100 150 - 250 - 300 - 500 750 - 1000 - 1500 Kg	
SB/TCC-1		Amortiguador cilindrico para células TCC-1	
CO-2		2000-3000-4000 Kg	
SB/CO-2		Amortiguador cilindrico para células CO-2	
TRACCIÓN - COMPRESIÓN		TOLVAS - DEPÓSITOS - SILOS	
S - 1		30 - 50 - 75 - 100 150 Kg	
ROT/S-1		Rótula para tracción S-1	
S - 2A		300 - 500 - 750 1000 Kg	
ROT/S-2A		Rótula para tracción S-2A	
S - 2B		750 - 100 - 1500 2000 - 2500 Kg 3 - 5 - 6 - 10 Tn	
ROT/S-2B		Rótula para tracción S-2B	
		BASCULAS SUSPENDIDAS	

